

BRYANT® Wiring Devices

Manufactured Structures
Plant Maintenance and Repair



EXTRA HEAVY DUTY INDUSTRIAL SPECIFICATION GRADE

Description	Catalog Number
20 Amp 120-277V AC; Single-Pole; Lock type switch; back and side wired; straight-key included	4901L

TOGGLE AC MOTOR CONTROLLERS AND ENCLOSED SWITCHES SUITABLE AS DISCONNECTS

Description	Amp	Phase	Poles	HP Ratings				Catalog Number
				120V AC	240V AC	480V AC	600V AC	
Toggle switch	30	1	2	2	5	10	15	30002D
Toggle switch	30	3	3	3	7.5	15	20	30003D
NEMA 1 aluminum - toggle	30	1	2	2	5	10	15	30102D
NEMA 1 aluminum - toggle	30	3	3	3	7.5	15	20	30103D

PENDANT CONTROL STATIONS

Description	Catalog Number
Single speed with mechanical interlock between push buttons; Ideal for use on outdoor equipment.	PCS002

PORTABLE GFCI - SINGLE AND TRIPLE TAP 15A 120V AC



Description	Catalog Number	
	Automatic Set	Manual Set
2' (60.9 cm) GFCI line cord; single	GFC2A	GFC2M
2' (60.9 cm) GFCI line cord; triple tap	GFCI15125TRIA	GFCI15125TRIM

DELUXE STRAIN RELIEF CORD GRIPS

N.P.T. Hub Size	Straight Male Thread	Grip Dia. Range Inches (cm)
½	DC3712	.375-.500 (.95-1.27)
	DC5012	.500-.625 (1.27-1.59)
¾	DC5034	.500-.625 (1.27-1.59)
	DC6234	.625-.750 (1.59-1.90)
1	DC751	.750-.875 (1.90-2.22)
	DC871	.875-1.000 (2.22-2.54)

DUST-TIGHT GRIPS

N.P.S./N.P.T.* Hub Size	Catalog Number	Cable Diameter Range Inches (cm)	Mesh Length Inches (cm)
½ N.P.S.	BDSR43	.43-.54 (1.09-1.37)	4¾ (12.06)
¾ N.P.S.	BDSR54	.54-.73 (1.37-1.85)	6½ (16.51)
1 N.P.S.	BDSR73	.73-.97 (1.85-2.46)	7 (17.78)

Note: *N.P.S. = National Pipe Straight; N.P.T. = National Pipe Taper.

LIQUID-TIGHT GRIPS

Conduit Trade Size	Catalog Number	Mesh Length Inches (cm)	N.P.T. Hub Size
½	FC50	4 (10.16)	½
¾	FC75	4 (10.16)	¾
1	FC100	5 (12.70)	1



NOTES: